



SPECIFICATION DATA SHEET

N-9080

Non Asbestos Soft Gasket Material

Description

N-9080 is a mix of reinforced fibres & NBR compositions with outstanding sealing characteristics. This material is an economical alternative for soft gasket applications like Oil/Fuel/Water areas, Carburetors, Gearboxes, Oil Pans, Material Handling Equipment, Chemical Pumps & pipe Lines, Diesel Engines etc. Max operating temperature upto 150°C. Available in Grey colour.

S.NO.	PROPERTY		SPECIFICATIONS	TEST METHOD
1.	DENSITY	gm/cc	0.90-1.05	ASTM F-1315
2.	COMPRESSIBILITY	%	30 (max)	ASTM F-36
	AT70 kg/cm ² (1000 psi)			
3.	RECOVERY	%	35 (min)	ASTM F-36
4.	TENSILE STRENGTH	kg/cm ²	100 (min)	ASTM F-152
5.	FLUID RESISTANCE			
	ASTM OIL NO 3		-----	ASTM F-146
	THICKNESS INCREASE	%	10 (max)	
	WEIGHT INCREASE	%	45 (max)	
	ASTM FUEL B		-----	ASTM F-146
	THICKNESS INCREASE	%	10 (max)	
	WEIGHT INCREASE	%	45 (max)	
	GLYCOL WATER 50/50		-----	ASTM F-146
	THICKNESS INCREASE	%	30 (max)	
	WEIGHT INCREASE	%	60 (max)	
6.	BINDER TYPE		Nitrile Butadine	

Remarks & Related Data

Specification values determined by test methods required for ASTM F-104, TYPE 3 MATERIALS

Availability

- Roll Width : 1200mm
- Roll Weight : 50 - 250 kg
- Thickness Range : 0.30mm - 1.50mm
- Core Size : 75mm

Other special sizes available on request. Anti stick coating on request.

Aeroflex Sealing Material Mfg. Co.

(An ISO 9001-2015 Certified Company)

Correspondence Address :
 16/15, East Patel Nagar, New Delhi-110008, India
 Tel.: +91-11-25885717, 25880084
 Works Address :
 43, KM. Stone, Delhi-Rohtak Highway, (NH-10), V. & P.O. Rohad,
 Distt. Jhajjar, Bahadurgarh-124501, Haryana, India
 Email : Info@aeroflexsealing.com
 Website : www.aeroflexsealing.com



ISO 9001:2015

